# **Material Safety Data Sheet**

## **Product Identification**

#### PRODUCT NAME NX Neugloss

<Supergloss>

**PRODUCT CODE** NX200, NX300, & NX500

TYPE OF MATERIALS Acrylic Laminate

### PRODUCT DESCRIPTION

NX Neugloss- Supergloss are versatile and can be used for various applications, including kitchen cabinets, countertops, wall panels, furniture and more. It offers a subdued, soft, and velvety appearance that reduces glare and reflection.



#### Urban Republic Pty Ltd ABN: 77 133 990 306

49 Metrolink Circuit, Campbellfield VIC 3061, Australia

nxdecor.com.au

contact +613 9357 0934 +613 9357 8303

емань info@urbanrepublic.com.au

## **Storage and Transport**

When handling NX Neugloss- Supergloss manually, always wear protective gloves to prevent cuts. Ensure it is stored away from ignition sources, heat, and flammable products to maintain safety.

### **First Aid**

Inhalation	Inhalation of dust or fumes emitted by thermal action may cause respiratory tract irritation. If exposed to vapors generated at elevated temperatures, remove the patient from the contaminated area, seek medical attention.
Contact with Skin	No effects expected from contact with the product at room temperature. May cause irritation and/or cutting by mechanical action. The melted product causes burns. In case of contact with molten material, the skin should be cooled immediately with cool water and call your doctor. Do not remove the product that is solidified on the skin. Treat as frostbite.
Contact with Eyes	Eye contact with vapors emitted by thermal action in a misuse of the product can cause irritation and redness. Sprinkle with water if irritation persists seek medical attention.
Ingestion	The ingestion may cause abdominal pain. No specific measures are required in case of ingestion, as it is. If necessary, call a doctor.



# **Material Safety Data Sheet**

# **Environmental Aspects In Use**

The product is safe for human health in the way it is sold in the market and the way it is treated on normal procedures of storage and handling. In the melted state it may cause burns. The product is not dangerous according to criteria established by the European union. The product is stable and inert in terms of storage and use. There are no critical hazards, and it is environmentally safe.

## **Use & Care**

- Avoid using the surface as a chopping, slicing, or hammering surface: NX Neugloss- Supergloss are not designed for cutting or pounding, so always use a proper cutting board or suitable surface to protect them.
- Avoid exposing to high temperatures: Prolonged exposure to temperatures exceeding 60 °C (140 °F) can lead to laminate separation from the substrate. Be mindful of heat sources and use protective measures when necessary.
- Refrain from using sharp tools: To prevent scratches or damage, do not use knives, box-cutters, or other sharp objects directly on NX Neugloss- Supergloss surface. Instead, use appropriate cutting surfaces.
- Prevent water-related issues: Do not flood the laminate surface and take care not to introduce water at joints or seams to prevent substrate expansion and potential damage.

#### Urban Republic Pty Ltd ABN: 77 133 990 306

49 Metrolink Circuit, Campbellfield VIC 3061, Australia

nxdecor.com.au

сонтаст +613 9357 0934 +613 9357 8303

емань info@urbanrepublic.com.au



## **First Aid**

Extinguishing Means	Water, water spray, foam, dry chemical, carbon dioxide. Cool containers with water spray.
Physical Hazard of Exposure	In case of fire can emit smoke composed of water, carbon dioxide, nitrogen, carbon oxide, carbon dioxide (CO2) and fumes.
Personal Protective Equipment	Use appropriate personal protective equipment (scuba, helmet, goggles, overalls, gloves, and boots flame retardant).